

# INCATI

Innovative Carpet Tiles

## CORAL - CORAL LINES

version 27/09/2019  
replaces 13/09/2019

Výrobní postup			<b>všiváný 1/10"</b>
Typ vlákn			<b>smyčka</b>
Materiál vlasu			<b>100% PA 6 BCF</b>
Metoda barvení			<b>barveno roztokem</b>
Podklad			<b>bitumen</b>
Hmotnost vlasu	ISO 2424	g/m2	<b>485</b> (+/-)
Celková hmotnost	ISO 8543	g/m2	<b>4.200</b> (+/-)
Výška vlasu	ISO 1766	mm	<b>3,0</b> (+/-)
Celková výška	ISO 1765	mm	<b>5,5</b> (+/-)
Počet vpichů	ISO 1763	/m2	<b>175.000</b> (+/-)
Rozměr		cm	<b>50 x 50</b>
Balení			<b>20 v balení 5 m2</b>
Klasifikace	EN 1307		<b>33</b> komerční vysoká
Třída komfortu	EN 1307		<b>LC 1</b>
Kolečková židle	EN 985		<b>A</b>
Prostorová stabilita	EN 986		<b>≤ 0,2%</b>
Hořlavost	EN 13501-1		<b>Bfl-S1</b>
Elektrostatické vlastnosti	ISO 6356	kV	<b>≤ 2,0</b>
	ISO 10965	Ω	<b>≥ 10<sup>10</sup></b>
Tepelná odolnost	ISO 8302	m2/K/W	<b>0,066</b>
Absorpce zvuku	ISO 354	α <sub>w</sub>	<b>0,15</b>
	ISO 10140	ΔL <sub>w</sub>	<b>23 dB</b>
	ISO 10140	ΔL	<b>35 dB</b> (1000 Hz)
Barevná stálost světlo	ISO 105 B02		<b>≥ 8</b>
Stálost při oděru	ISO 105 X12		<b>≥ 4-5</b>
	DIBt Nr.		<b>Z-156.601-1467</b>



**SDN**  
solution dyed nylon  
Stoach clearable yarn

 19 <b>EN 14041</b> DOP 000583T-001	 Bfl-S1
	 DS
TAPIBEL NV Industrielaan 4 B-3900 Pelt Belgium +32 11 80 48 50 sales@incati.be www.incati.be	 DL PCP
	 NA HCHO
<b>EN 1307</b> for use as floorcovering in buildings (EN 14041) according to the manufacturer's specification	



### TÜV Emission testing

Results comply with emission threshold of


- AgBB - Germany
- Belgian VOC regulation
- BREEAM Exemplary level
- French VOC regulation
- LEED V4 (outside North America)



### INSTALLATION



### ALSO AVAILABLE



### MAINTENANCE

visit our website [www.incati.be/en/faq-carpet-tiles](http://www.incati.be/en/faq-carpet-tiles)  
for more detailed information

These technical details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request, if available. We reserve the right to alter specifications without notice. Due to the method of manufacture, perfect pattern/colour matching cannot be guaranteed.

Shading/pile reversal might occur in cut pile carpets, without affecting overall quality and suitability. It is not considered as a manufacturing fault.