



| | |
|----------------------------|--|
| Construction | Tufted Cut Pile Carpet |
| Yarn | 100% Solution Dyed Nylon |
| Width | 4.0m |
| Standard Roll Length | 35m |
| Yarn Weight | 1200g/m ² / 36oz/yd ² |
| Total Weight | 2310g/m ² |
| Total Thickness | 10.7mm |
| Machine Gauge | 1/8th |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | Cosyback |
| Electrical Properties | Antistatic |
| Electrical Propensity | ≤ 2kV |
| Fire Rating | ISO 9239-1 |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Underfloor Heating | Suitable |
| Rating | Extra Heavy Duty Residential |
| Stair Rating | Suitable |
| Warranties | 15 Year General Warranty 15 Year Residential Wear Warranty 15 Year Stain Resistant Warranty 15 Year Fade Resistant Warranty 15 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty 3 Year Commercial Wear Warranty |
| Environmental | GUT Label GreenStar, Homestar™, Well Building Standard® Environmental Product Declaration Low VOC, solution dyeing uses no water ISO 14001 |
| Installation | Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.